



Schottky Rectifier



Features

- Ideal for automated placement
- Low power losses
- High forward surge capability
- Meets MSL level1, per J-STD-020, LF maximum peak of 260 °C
- Part no. with suffix "Q" means AEC-Q101 qualified

Typical Applications

For use in lighting, fast switching rectification of power suppliers, DC/AC inverters, DC/DC converters, and freewheeling diodes for polarity protection application for consumer, automotive and telecommunication.

Mechanical Data

- **Package:** TO-277
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS10U100JBQ
Device marking code			SS10U100JB
Repetitive Peak Reverse Voltage	V _{RRM}	V	100
Average Rectified Output Current @60Hz -sine wave	I _O	A	10
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, T _a =25°C	I _{FSM}	A	280
Current Squared Time @1ms≤t≤8.3ms T _J =25°C	I ² t	A ² s	325
Storage Temperature	T _{stg}	°C	-55 ~+175
Junction Temperature	T _J	°C	-55 ~+175

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Typ	Max	
Instantaneous forward voltage	V _F	V	I _F =5A	T _A =25°C	0.74	-
			I _F =10A		0.79	0.88
			I _F =5A	T _A =125°C	0.59	-
			I _F =10A		0.65	0.74
Typical junction capacitance	C _J	pF	V _R =4V, f=1 MHz	270	-	
Leakage Current	I _R	nA	V _R =100V	T _A =25°C	10	1000
		uA		T _A =125°C	45	200



SS10U100JBQ

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS10U100JBQ
Typical Thermal Resistance	R _{θJ-A}	°C/W	65 ⁽¹⁾
	R _{θJ-A}	°C/W	100 ⁽²⁾
	R _{θJ-C}	°C/W	8 ⁽¹⁾
	R _{θJ-L}	°C/W	3 ⁽²⁾

Note


(1) Thermal resistance from junction to case mounted on P.C.B. with 16mm*16mm copper pad areas

(2) Thermal resistance from junction to case mounted on P.C.B. with 10mm*10mm copper pad areas

■ Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SS10U100JBQ	F1	Approximate 0.106	5000	80000	13" reel

■ Marking Information



Note:

1. All marking is at middle of the product body
 2. All marking is in laser printing
 3. XXXXXX is part no., like SS10U100JB.
 4. Body color: Black
 5. YWW is date code, "Y" is year. "WW" is week.
- For instance: The 15th week of 2019, date code is 915



SS10U100JBQ

■ Characteristics (Typical)

Fig.1: Maximum Forward Current Derating Curve




Fig.2: Forward Surge Current Capability




Fig.3: Typical Instantaneous Forward Characteristics






Fig.4: Typical Reverse Leakage Characteristics




■ Outline Dimensions



DIM	mm	
	MIN.	MAX.
A	3.90	4.10
B	1.70	1.90
C	6.40	6.60
D	5.30	5.50
E	0.80	1.00
F	1.85 ref.	
G	0.35	0.45
H	1.10	1.20
I	4.10	4.50
J	1.50	1.90
K	2.90	3.40
L	0.55	0.75
M	0.50 ref.	
N	1.15 ref.	



■ Suggested pad layout



DIM	MIN.(mm)
A	3.36
B	4.86
C	0.85
P	1.84
Q1	1.40
Q2	1.40



SS10U100JBQ

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, lifesaving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.